

## TMPD4-00380800-30S

380~8000 MHz, 30W, SMA Female  
4-WAY POWER DIVIDER

### Electrical Characteristics

<b>FREQUENCY RANGE</b>	.....	380~8000MHz
<b>INSERTION LOSS</b>	.....	2.0dB max.
(excluding theoretical insertion loss 6.0dB)		
<b>AMPLITUDE BALANCE</b>	.....	±0.3dB
<b>PHASE BALANCE</b>	.....	±4 Deg.
<b>VSWR(input port)</b>	.....	1.18 typ. & 1.25 max.
<b>VSWR(output ports)</b>	.....	1.12 typ. & 1.22 max.
<b>ISOLATION</b>	.....	26dB typ. & 20dB min.
<b>IMPEDANCE</b>	.....	50 Ohms
<b>POWER RATING(as a divider)</b>	.....	30W
<b>POWER RATING(as a combiner)</b>	.....	2W

### Mechanical and Enviromental Characteristics

<b>Dimensions</b>	.....	130×58×10mm
<b>RF Connectors</b>	.....	SMA female
<b>Surface Finishing</b>	.....	Black Paint
<b>Operating Temperature</b>	.....	-45℃ ~ +85℃
<b>Weight</b>	.....	200g

### Outline Drawing(mm[inch])

