

## TMPD4-01401800-20S

1.4 to 18 GHz, 20W, SMA Female  
4-WAY POWER DIVIDER

### Electrical Characteristics

<b>FREQUENCY RANGE</b>	.....	1400~18000MHz
<b>INSERTION LOSS</b>	.....	2.6dB max.
(excluding theoretical insertion loss 6.0dB)		
<b>AMPLITUDE BALANCE</b>	.....	±0.4dB
<b>PHASE BALANCE</b>	.....	±5 Deg.
<b>VSWR(input port)</b>	.....	1.19 typ. & 1.55 max.
<b>VSWR(output ports)</b>	.....	1.12 typ. & 1.5 max.
<b>ISOLATION</b>	.....	24dB typ. & 16dB min.
<b>IMPEDANCE</b>	.....	50 Ohms
<b>POWER RATING(as a divider)</b>	.....	20W
<b>POWER RATING(as a combiner)</b>	.....	1W

### Mechanical and Environmental Characteristics

<b>Dimensions</b>	.....	99×71×10mm
<b>RF Connectors</b>	.....	SMA female
<b>Surface Finishing</b>	.....	Black Paint
<b>Operating Temperature</b>	.....	-45℃ ~ +85℃
<b>Weight</b>	.....	175g

### Outline Drawing(mm[inch])

