


## TMPD4-02400590-50N

2.4 to 5.9 GHz, 50W, N Female  
4-WAY POWER DIVIDER

### Electrical Characteristics

<b>FREQUENCY RANGE</b>	.....	2400~5900MHz
<b>INSERTION LOSS</b>	.....	0.6dB max.
(excluding theoretical insertion loss 6.0dB)		
<b>AMPLITUDE BALANCE</b>	.....	±0.2dB
<b>PHASE BALANCE</b>	.....	±3 Deg.
<b>VSWR(input port)</b>	.....	1.18 typ. & 1.3 max.
<b>VSWR(output ports)</b>	.....	1.16 typ. & 1.2 max.
<b>ISOLATION</b>	.....	28dB typ. & 18dB min.
<b>IMPEDANCE</b>	.....	50 Ohms
<b>POWER RATING(as a divider)</b>	.....	50W
<b>POWER RATING(as a combiner)</b>	.....	3W

### Outline Drawing(mm[inch])



### Mechanical and Environmental Characteristics

<b>Dimensions</b>	.....	70×110×22mm
<b>RF Connectors</b>	.....	N female
<b>Surface Finishing</b>	.....	Sandblasted Silver
<b>Operating Temperature</b>	.....	-35°C ~ +75°C
<b>Weight</b>	.....	500g