

## TMPD8-00300150-30S

300 to 1500 MHz, 30W, SMA Female  
 8-WAY POWER DIVIDER

### Electrical Characteristics

<b>FREQUENCY RANGE</b>	.....	300~1500MHz
<b>INSERTION LOSS</b>	.....	1.4dB max.
(excluding theoretical insertion loss 9.0dB)		
<b>AMPLITUDE BALANCE</b>	.....	±0.4dB
<b>PHASE BALANCE</b>	.....	±5 Deg.
<b>VSWR(input port)</b>	.....	1.18 typ. & 1.25 max.
<b>VSWR(output ports)</b>	.....	1.12 typ. & 1.2 max.
<b>ISOLATION</b>	.....	26dB typ. & 20dB min.
<b>IMPEDANCE</b>	.....	50 Ohms
<b>POWER RATING(as a divider)</b>	.....	30W
<b>POWER RATING(as a combiner)</b>	.....	2W

### Mechanical and Environmental Characteristics

<b>Dimensions</b>	.....	168×120×10mm
<b>RF Connectors</b>	.....	SMA female
<b>Surface Finishing</b>	.....	Black Paint
<b>Operating Temperature</b>	.....	-45°C ~ +85°C

### Outline Drawing(mm[inch])

