


## TMPD8-04001200-20S

**4 to 12 GHz, 20W, SMA Female  
 8-WAY POWER DIVIDER**

### Electrical Characteristics

<b>FREQUENCY RANGE</b>	.....	4000~12000MHz
<b>INSERTION LOSS</b>	.....	1.5dB max. (excluding theoretical insertion loss 9.0dB)
<b>AMPLITUDE BALANCE</b>	.....	±0.2dB
<b>PHASE BALANCE</b>	.....	±4 Deg.
<b>VSWR(input port)</b>	.....	1.2 typ. & 1.4 max.
<b>VSWR(output ports)</b>	.....	1.2 typ. & 1.3 max.
<b>ISOLATION</b>	.....	24dB typ. & 18dB min.
<b>IMPEDANCE</b>	.....	50 Ohms
<b>POWER RATING(as a divider)</b>	.....	20W
<b>POWER RATING(as a combiner)</b>	.....	1W

### Outline Drawing(mm[inch])



### Mechanical and Environmental Characteristics

<b>Dimensions</b>	.....	70×112×10mm
<b>RF Connectors</b>	.....	SMA female
<b>Surface Finishing</b>	.....	Blue Paint
<b>Operating Temperature</b>	.....	-45°C ~ +85°C
<b>Weight</b>	.....	240g