

Product Features

- High power handling up to 200W
- Low Insertion Loss
- High isolation within operational band
- Custom design available upon request
- TAB Connector type
- Operating temperature range -30°C ~ +70°C



SPECIFICATIONS

Outline Drawing(mm[inch])	Model Number	Frequency Range (MHz)	Insertion Loss (dB. max.)	Isolation (dB. min.)	VSWR (max.)	Forward Power (W)	Reverse Power (W)
Front View 	TSMI3611-01290130-200	1296~1298	0.2	30	1.15	200	10
	TSMI3611-01100170-200	1100~1700	0.5	15	1.45	200	10
	TSMI3611-01000130-200	1000~1300	0.4	20	1.25	200	10
Side View 	TSMI3611-00900093-200	900~930	0.2	30	1.15	200	10
	TSMI3611-860M872M-200	860~872	0.25	30	1.15	200	10
	TSMI3611-770M860M-200	770~860	0.3	23	1.2	200	10
	TSMI3611-00700100-200	700~1000	0.6	16	1.4	200	10
	TSMI3611-00700090-200	700~900	0.4	20	1.25	200	10
	TSMI3611-00600080-200	600~800	0.5	19	1.25	200	10
	TSMI3611-00450052-200	450~520	0.4	20	1.25	200	10
	TSMI3611-00440047-200	440~470	0.3	23	1.2	200	10
	TSMI3611-419M425M-200	419~425	0.3	30	1.15	200	10
	TSMI3611-413M419M-200	413~419	0.3	30	1.15	200	10
Back View 	TSMI3611-00400047-200	400~470	0.4	20	1.25	200	10
	TSMI3611-00390041-200	390~410	0.3	23	1.2	200	10
	TSMI3611-00380046-200	380~460	0.5	18	1.3	200	10
	TSMI3611-00350037-200	350~370	0.35	21	1.2	200	10
	TSMI3611-309M339M-200	309~339	0.4	20	1.25	200	10
	TSMI3611-260M280M-200	260~280	0.5	20	1.25	200	10
	TSMI3611-240M260M-200	240~260	0.5	18	1.3	200	10
	TSMI3611-220M240M-200	220~240	0.65	18	1.3	200	10