

FEATURES

- Small Size
- High Accuracy
- High Stability

APPLICATIONS

- Laboratory Test and Measurement
- Wireless Communication



Electrical Specifications

Frequency Range	2~3GHz
Impedance	50Ω or 75Ω nominal
Attenuation Range	0~10dB in 1dB steps
Attenuation Steps(dB)	1, 2, 3, 4
VSWR	1.5 max
Accuracy	±0.5dB max
Insertion Loss	2.5dB max
Average Power	10W
Operating Voltage	+12V
	(TTL Controlled with drive circuit)
Operating Current	100mA max
Temperature Range	-40°C~+70°C
RoHS Status	RoHS Compliant

Mechanical Specifications

RF Connector	SMA, N, BNC
Connector Body	Gold Plated Brass
Female Pin	Gold Plated Beryllium Cooper
Housing	Aluminum, Anodic Oxidation
Size	125×51×23mm
Weight	160g

Ordering Information

10W	PA	3	-	4	-	10	-	50	S	T
									Control	
									T: TTL	
									RF Connector	
									S: SMA	
									N: Type N	
									B: BNC	
									Impedance	
									50: 50Ω	
									75: 75Ω	
									Total dB Value	
									Cells No.	
									Maximum Frequency(GHz)	
									Programmable Attenuator	
									Average Power(W)	

◇ Test Data is available at an additional cost ◇