

TA760S

Low Loss Phase Stable Cable Assembly
DC~18GHz

TITAN MICROWAVE INC.



Features

- Low Loss
- High Phase Stability
- Excellent Performance
- Well Durability
- Suitable for All Kinds of Harsh Environment

Applications

- Laboratory
- Wireless Communications
- Phased Array Radar
- Avionics

Specifications

Electrical

- Operating Frequency DC~18GHz
- Cutoff Frequency 18GHz
- Impedance 50Ω
- Velocity of Propagation 83%
- Screening Effectiveness 90dB min
- PIM -155dBc
- Voltage Rating 2500V, DC
- Phase Stability <750ppm@-55°C~+85°C

Environmental & Mechanical

- Operating Temperature -55°C~+165°C
- Min Bending Radius/Single 38.00 mm
- Min Bending Radius/Repeated 76.00 mm
- Weight 120g/m

Attenuation@25°C & Power@40°C (sea level)

Frequency(GHz)	1	2	3	6	8	10	12.4	16	18
Attenuation(dB/100m)	16.7	23.8	29.3	42.1	48.9	55	61.7	70.7	75.3
Power Handling(W)	1604	1125	913	637	548	487	435	379	356

Construction

Inner Conductor	Solid Silver-plated Copper	2.39 mm
Dielectric	Low Density PTFE	6.25 mm
Inner Shield	Silver-plated Copper Tape	6.49 mm
Outer Shield	Silver-plated Copper Braid	7.06 mm
Jacket	Gray FEP	7.65 mm

Outline



Ordering Information

TA 7 6 0 S - 1 8 - S F S F - 1

Cable Code

Operating Frequency(GHz)

RF Connectors(S:SMA)

SS: SMA male to SMA male

SSF: SMA male to SMA female

SFSF: SMA female to SMA female

Overall Length(meter(s))

For other connector options, contact factory.