

TMDC-04001800-10S50A 4-18 GHz, 10dB, 50W, SMA(m-f)

FEATURES

- ❖ Wide Band Operation 4-18GHz
- ❖ Power Handle Capability up to 50W
- ❖ 10 dB Typical Coupling
- ❖ Low Insertion Loss


APPLICATIONS

- ❖ Frequency Measurements
- ❖ Signal Levelling, Signal Sampling
- ❖ Signal Injection
- ❖ Reflection Coefficient Measurements
- ❖ Measure incident and reflected power to determine VSWR

SPECIFICATIONS

Parameters	Min.	Typ.	Max.	Units
Frequency Range	4	-	18	GHz
Impedance	-	50	-	Ohms
Nominal Coupling	9	10	11	dB
Frequency Sensitivity	-	±0.5	±0.7	dB
Directivity	12	15	-	dB
Insertion Loss(Excluding coupling loss)	-	-	0.7	dB
Insertion Loss(True)	-	1.0	1.2	dB
VSWR Primary	-	1.3	1.5	:1
VSWR Secondary	-	1.3	1.5	:1
Average Power	50			W
Peak Power	500(10% Duty Cycle, 1µs Pulse Width)			W
Operating Temperature	-40°C~+85°C			
Storage Temperature	-50°C~+105°C			
Input/Output Connectors	SMA female/female/male			
Weight	35g			
Surface Finishing	Gray Paint			
Material	Aluminum			

Outline Drawing [mm[inch]]



Tolerances ±0.5[0.02]