

TMDC-04001800-20N50 4-18 GHz, 20dB, 50W, N Female

FEATURES

- ❖ Wide Band Operation 4-18GHz
- ❖ Power Handle Capability up to 50W
- ❖ 20 dB Typical Coupling
- ❖ Low Insertion Loss


APPLICATIONS

- ❖ Frequency Measurements
- ❖ Signal Levelling, Signal Sampling
- ❖ Signal Injection
- ❖ Reflection Coefficient Measurements
- ❖ Measure incident and reflected power to determine VSWR

SPECIFICATIONS

Parameters	Min.	Typ.	Max.	Min.	Typ.	Max.	Units
Frequency Range	4	-	10	10	-	18	GHz
Impedance	-	50	-	-	50	-	Ohms
Nominal Coupling	19	20	21	19	20	21	dB
Frequency Sensitivity	-	±0.5	±0.6	-	±0.6	±0.8	dB
Directivity	14	18	-	12	14	-	dB
Insertion Loss(Excluding coupling loss)	-	-	0.4	-	-	0.6	dB
Insertion Loss(True)	-	0.25	0.5	-	0.4	0.7	dB
VSWR Primary	-	1.2	1.3	-	1.3	1.5	:1
VSWR Secondary	-	1.2	1.3	-	1.4	1.5	:1
Average Power	50						W
Peak Power	500(10% Duty Cycle, 1µs Pulse Width)						W
Operating Temperature	-40°C~+85°C						
Storage Temperature	-50°C~+105°C						
Input/Output Connectors	N female						
Weight	115g						
Surface Finishing	Gray Paint						
Material	Aluminum						

Outline Drawing [mm[inch]]



Tolerances ±0.5[0.02]