

TMDC-09001100-15S30 9-11 GHz, 15dB, 30W, SMA Female

FEATURES

- ❖ Band Operation 9-11 GHz
- ❖ Power Handle Capability up to 30W
- ❖ 15 dB Typical Coupling
- ❖ Low Insertion Loss


APPLICATIONS

- ❖ Frequency Measurements
- ❖ Signal Levelling, Signal Sampling
- ❖ Signal Injection
- ❖ Reflection Coefficient Measurements
- ❖ Measure incident and reflected power to determine VSWR

SPECIFICATIONS

Parameters	Min.	Typ.	Max.	Units
Frequency Range	9	-	11	GHz
Impedance	-	50	-	Ohms
Nominal Coupling	14	15	16	dB
Frequency Sensitivity	-	-	±0.7	dB
Directivity	15	-	-	dB
Insertion Loss(Excluding coupling loss)	-	-	0.7	dB
VSWR Primary	-	1.18	1.4	:1
VSWR Secondary	-	1.18	1.4	:1
Average Power	30			W
Operating Temperature	-45°C~+85°C			
Storage Temperature	-50°C~+105°C			
Input/Output Connectors	SMA female			
Weight	35g			
Surface Finishing	Black Paint			
Material	Aluminum			

Outline Drawing [mm[inch]]



Tolerances ±0.5[0.02]