

TMHC90-00470086-250N 0.47-0.86 GHz, 250W, N Female

FEATURES

- ❖ Wide Band Operation 0.47-0.86 GHz
- ❖ Power Handle Capability up to 250W
- ❖ High Isolation Across Operational Band
- ❖ Low Insertion Loss
- ❖ Stable Performance Over Temperature


APPLICATIONS

- ❖ Commercial Wireless Communications
- ❖ Radar Systems
- ❖ Receivers Sytems
- ❖ Antenna Beam Forming
- ❖ Test Labs

SPECIFICATIONS

Parameters	Min.	Typ.	Max.	Units
Frequency Range	0.47	-	0.86	GHz
Impedance	-	50	-	Ohms
Nominal Coupling	-	3	-	dB
Insertion Loss	-	-	0.4	dB
Isolation	25	-	-	dB
Amplitude Balance	-	-	±0.4	dB
Phase Balance	-	-	±2	Deg
VSWR	-	-	1.2	:1
Average Power	-	-	250	W
Peak Power	-	-	3	kW
Operating Temperature	-40°C~+85°C			
Storage Temperature	-50°C~+105°C			
Input/Output Connectors	N female			
Weight	490g			
Surface Finishing	Black/Blue Paint			
Material	Aluminum			

Outline Drawing [mm[inch]]



Tolerances ±0.5[0.02]