

TMDC-10004000-20K20 10-40 GHz, 20dB, 20W, 2.92mm Female

FEATURES

- ❖ Band Operation 10-40 GHz
- ❖ Power Handle Capability up to 20W
- ❖ 20 dB Typical Coupling
- ❖ Low Insertion Loss


APPLICATIONS

- ❖ Frequency Measurements
- ❖ Signal Levelling, Signal Sampling
- ❖ Signal Injection
- ❖ Reflection Coefficient Measurements
- ❖ Measure incident and reflected power to determine VSWR

SPECIFICATIONS

Parameters	Min.	Typ.	Max.	Units
Frequency Range	10	-	40	GHz
Impedance	-	50	-	Ohms
Nominal Coupling	19	20	21	dB
Frequency Sensitivity	-	-	±1.0	dB
Directivity	10	-	-	dB
Insertion Loss(Excluding coupling loss 0.04dB)	-	-	1.2	dB
VSWR Primary	-	-	1.6	:1
VSWR Secondary	-	-	1.6	:1
Average Power	-	-	20	W
Operating Temperature	-45	-	+85	°C
Storage Temperature	-50	-	+105	°C
Input/Output Connectors	2.92mm female			
Weight	30g			
Surface Finishing	Black/Blue Paint			
Material	Aluminum			

Outline Drawing [mm[inch]]



Tolerances ±0.5[0.02]