

TMDC-00950200-20N500 0.95-2 GHz, 20dB, 500W, N Female

FEATURES

- ❖ Wide Band Operation 0.95-2 GHz
- ❖ High Power Handle Capability up to 500W
- ❖ 20 dB Typical Coupling
- ❖ Low Insertion Loss


APPLICATIONS

- ❖ Frequency Measurements
- ❖ Signal Levelling, Signal Sampling
- ❖ Signal Injection
- ❖ Reflection Coefficient Measurements
- ❖ Measure incident and reflected power to determine VSWR

SPECIFICATIONS

Parameters	Min.	Typ.	Max.	Units
Frequency Range	0.95	-	2	GHz
Impedance	-	50	-	Ohms
Nominal Coupling	19	20	21	dB
Frequency Sensitivity	-	-	±1.0	dB
Directivity	20	-	-	dB
Insertion Loss(Excluding coupling loss 0.04dB)	-	-	0.3	dB
VSWR Primary	-	-	1.2	:1
VSWR Secondary	-	-	1.2	:1
Power Handling	Incident	-	500	W
	Reflected	-	50	W
Operating Temperature	-55	-	+85	°C
Input/Output Connectors	N-Female			
Weight	260g			
Surface Finishing	Black/Blue Paint			
Material	Aluminum			

Outline Drawing [mm[inch]]



Tolerances ±0.5[0.02]