
## TMPD2-00700270-30S

| REV. | DATE      | COMMENTS            | INITIAL |
|------|-----------|---------------------|---------|
| 1    | 2021/8/18 | ENGINEERING RELEASE |         |

## **Electrical Data**

| Frequency Range           | 0.7~2.7 GHz   |
|---------------------------|---------------|
| Insertion Loss            | ≤0.6 dB       |
| (excluding theoretical lo | oss 3.0dB)    |
| VSWR(input)               | ≤1.20         |
| VSWR(output)              | ≤ 1.20        |
| Isolation                 | ≥20 dB        |
| Amplitude Balance         | ±0.2 dB       |
| Phase Balance             | ± 2°          |
| Impedance                 | 50 Ohm        |
| Average Power             | 30W (Forward) |
|                           | 2W (Reverse)  |



## **Mechanical Data**

Connector Dimensions Material Temperature Range SMA-Female 42  $\times$  38  $\times$  14mm Aluminum -35~+75°C

## Drawing not to scale, units:mm



www.titan-microwave.com Tel: +86 130 866 58398 Email: sales@titan-microwave.com chris@titan-microwave.com

| PART NUMBER<br>TMPD2-00700270-30S          |                          | DESCRIPTION<br>Power Divider, 2 Way, 0.7~2.7GHz, 30W<br>SMA-Female |
|--|--------------------------|--|
| CAGE CODE                                  | SIGNATURE                |  |
|  |                          |  |
| EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR |                          |  |
| THIS DRAWING OR SPEC                       | IFICATION IS PROPERTY OF |  |
| TITAN MICROWAVE INC.                       | IT IS ISSUED IN STRICT   |  |
| CONFIDENCE AND SHAL                        | L NOT BE REPRODUCED OR   |  |
| USED AS THE BASIS.                         |                          |  |

**RoHS** Compliant