## PART NUMBER

## TMDB-00567-VMVM

REV.	DATE	COMMENTS	INITIAL
1	2022/8/16	ENGINEERING RELEASE	

**RoHS Compliant** 

## **Electrical Data**

Frequency Range 0.005~67GHz


Insertion Loss≤ 0.7dBVSWR≤ 1.30DC Voltage60 VoltsImpedance50 Ohm

Operational Temperature  $-55^{\circ}\text{C} \sim +165^{\circ}\text{C}$ Storage Temperature  $-55^{\circ}\text{C} \sim +165^{\circ}\text{C}$ 

Body Material Stainless Steel 303

Inner Conductor Glod Plated Beryllium Copper Connectors 1.85mm-Male to 1.85mm-Male

Relative Humidity 0~90%



## Drawing not to scale, units:mm



www.titan-microwave.com Tel: +86 130 866 58398

Email: sales@titan-microwave.com chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TMDB-00	567-VMVM	DC Block, 0.005-67GHz, 60V 1.85mm-Male to 1.85mm-Male
CAGE CODE	SIGNATURE	
EXCEPT AS OTHERWISE	PROVIDED BY CONTRACTOR	
THIS DRAWING OR SPEC	IFICATION IS PROPERTY OF	
TITAN MICROWAVE INC.	IT IS ISSUED IN STRICT	
CONFIDENCE AND SHAL	L NOT BE REPRODUCED OR	
USED AS THE BASIS.		