PART NUMBER

TMDB-0127-SMSF

REV.	DATE	COMMENTS	INITIAL
1	2022/8/16	ENGINEERING RELEASE	

RoHS Compliant

Electrical Data

Frequency Range 0.01~26.5GHz

Insertion Loss≤ 0.6dBVSWR≤ 1.30:1DC Voltage≤ 50 Volts


Input Average Power 2W max@25°C (Derate linearly to 0.2W@100°C)

Impedance 50 Ohm

Operational Temperature -55°C~+100°C

Connectors SMA-Male to SMA-Female
Body Material Stainless Steel, Passiavted
Inner Conductor Glod Plated Beryllium Copper

Net Weight 5g







Drawing not to scale, units:mm



www.titan-microwave.com Tel: +86 130 866 58398

Email: sales@titan-microwave.com chris@titan-microwave.com

PART NUMBER		DESCRIPTION	
TMDB-0127-SMSF		Inner DC Block, 0.01-26.5GHz, 50V SMA-Male to SMA-Female	
CAGE CODE	SIGNATURE		
EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR			
THIS DRAWING OR SPEC	IFICATION IS PROPERTY OF		
TITAN MICROWAVE INC.	IT IS ISSUED IN STRICT		
CONFIDENCE AND SHAL	L NOT BE REPRODUCED OR		
USED AS THE BASIS.			