


PART NUMBER <b>TMDB-000318-SMSF</b>	REV.	DATE	COMMENTS	INITIAL
	1	2020/5/21	ENGINEERING RELEASE	

RoHS Compliant

**Electrical Data**

Frequency Range	0.0003~18 GHz
Insertion Loss	≤ 0.7dB
VSWR	≤ 1.35:1
DC Voltage	≤ 50 Volts
Impedance	50 Ohm
Operational Temperature	-40°C~+125°C
Storage Temperature	-55°C~+165°C
Body Material	Stainless Steel 303, Passivated
Inner Conductor	Gold Plated Beryllium Copper
Connectors	SMA-Male to SMA-Female



Drawing not to scale, units:mm



www.titan-microwave.com  
 Tel: +86 130 866 58398  
 Email: sales@titan-microwave.com  
 chris@titan-microwave.com

PART NUMBER <b>TMDB-000318-SMSF</b>		DESCRIPTION <b>DC Block, 0.0003-18GHz, 50V SMA-Male to SMA-Female</b>
CAGE CODE	SIGNATURE _____	
EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.		