#### PART NUMBER

## TMDB-0118-SSF

REV.	DATE	COMMENTS	INITIAL
1	2022/8/16	ENGINEERING RELEASE	

### **RoHS Compliant**

### **Electrical Data**

Frequency Range  $0.01\sim18~\text{GHz}$ Insertion Loss  $\leq 0.7\text{dB}$ VSWR  $\leq 1.30:1$ DC Voltage  $\leq 50~\text{Volts}$ 


Input Average Power 2W max@25°C (Derate linearly to 0.2W@100°C)

Impedance 50 Ohm


Operational Temperature -55°C~+100°C

Connectors SMA-Male to SMA-Female
Body Material Stainless Steel, Passiavted
Inner Conductor Glod Plated Beryllium Copper

Net Weight 5g







# Drawing not to scale, units:mm



www.titan-microwave.com Tel: +86 130 866 58398

Email: sales@titan-microwave.com chris@titan-microwave.com

PART NUMBER TMDB-0118-SSF		DESCRIPTION Inner DC Block, 0.01-18GHz, 50V SMA-Male to SMA-Female
CAGE CODE	SIGNATURE	
EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR		
THIS DRAWING OR SPECIFICATION IS PROPERTY OF		
TITAN MICROWAVE INC.	IT IS ISSUED IN STRICT	
CONFIDENCE AND SHALL	L NOT BE REPRODUCED OR	
USED AS THE BASIS.		