PART NUMBER

TMDB-0118-SSF100V

| REV. | DATE | COMMENTS | INITIAL |
|------|-----------|---------------------|---------|
| 1 | 2021/7/16 | ENGINEERING RELEASE | |

RoHS Compliant

Electrical Data

Frequency Range $0.01\sim18~\text{GHz}$ Insertion Loss $\leq 0.7\text{dB}$ VSWR $\leq 1.30:1$ DC Voltage $\leq 100~\text{Volts}$


Input Average Power 2W max@25°C (Derate linearly to 0.2W@100°C)

Impedance 50 Ohm


Operational Temperature -55°C~+100°C

Connectors SMA-Male to SMA-Female
Body Material Stainless Steel, Passiavted
Inner Conductor Glod Plated Beryllium Copper

Net Weight 5g







Drawing not to scale, units:mm



www.titan-microwave.com Tel: +86 130 866 58398

Email: sales@titan-microwave.com chris@titan-microwave.com

| PART NUMBER | | DESCRIPTION Inner DC Block, 0.01-18GHz, 100V | |
|--|------------------------|--|--|
| TMDB-0118-SSF100V | | SMA-Male to SMA-Female | |
| CAGE CODE | SIGNATURE | | |
| | | | |
| EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR | | | |
| THIS DRAWING OR SPECIFICATION IS PROPERTY OF | | | |
| TITAN MICROWAVE INC. | IT IS ISSUED IN STRICT | | |
| CONFIDENCE AND SHAL | L NOT BE REPRODUCED OR | | |
| USED AS THE BASIS. | | | |