


PART NUMBER <b>TMPD2-02000600-30SA</b>	REV.	DATE	COMMENTS	INITIAL
	A	2020/4/25	ENGINEERING RELEASE	

**Specifications**

Frequency Range	2-6GHz
Insertion Loss	0.5dB max (excluding theoretical insertion loss 3.0dB)
VSWR(Input)	1.3 max
VSWR(Output)	1.25 max
Isolation	20dB min
Amplitude Balance	± 0.3dB max
Phase Balance	± 4° max
Impedance	50 Ohm
Forward Power	30W max
Reverse Power	1W max
Peak Power	500W max
Connectors	SMA-Female
Connector Body	Stainless Steel, Passivated
Operating Temperature	-40°C~+70°C
Storage Temperature	-55°C~+85°C
Dimensions	35 × 30.5 × 12.7mm
Weight	50g max

RoHS Compliant



Drawing not to scale, units:mm



www.titan-microwave.com  
Tel: +86 130 866 58398  
Email: sales@titan-microwave.com  
chris@titan-microwave.com

PART NUMBER <b>TMPD2-02000600-30SA</b>		DESCRIPTION <b>Power Divider, 2 Way, 2-6GHz 30W, SMA-Female</b>
CAGE CODE	SIGNATURE	
EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.		