


PART NUMBER
TMPS12-00400800-2S

REV.	DATE	COMMENTS	INITIAL
1	2020/8/8	ENGINEERING RELEASE	

SPECIFICATIONS

Frequency Range 0.4-8GHz
 Insertion Loss 4.0dB max
 Isolation 80dB min
 Input&Output VSWR 1.6 max
 RF Input Power 2W
 Switching Speed 200ns max
 Voltage/Current +5Vdc@550mA max
 Connectors SMA-Female
 Control Connector DB9-Male
 Operating Temperature -40°C~+70°C
 Storage Temperature -55°C~+85°C
 Dimensions 160 × 58 × 18mm
 Material Aluminum 6061
 Surface Finish Nickel Plated



Drawing not to scale, units:mm

Control Truth Table

TTL Control Voltage Threshold				Low(0)=0V	High(1)=3.3V-5V
C4	C3	C2	C1	Signal Path State	
0	0	0	0	J0→J1	
0	0	0	1	J0→J2	
0	0	1	0	J0→J3	
0	0	1	1	J0→J4	
0	1	0	0	J0→J5	
0	1	0	1	J0→J6	
0	1	1	0	J0→J7	
0	1	1	1	J0→J8	
1	0	0	0	J0→J9	
1	0	0	1	J0→J10	
1	0	1	0	J0→J11	
1	0	1	1	J0→J12	
1	1	0	0	OFF	

PART NUMBER TMPS12-00400800-2S		DESCRIPTION PIN Diode Switch, SP12T, 0.4-8GHz, Absorptive, 2W, SMA-Female
CAGE CODE	SIGNATURE	
EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.		 <p>www.titan-microwave.com Tel: +86 130 866 58398 Email: sales@titan-microwave.com chris@titan-microwave.com</p>