


PART NUMBER
TMPS8-00400850-2S

REV.	DATE	COMMENTS	INITIAL
1	2020/8/8	ENGINEERING RELEASE	

SPECIFICATIONS

Frequency Range 0.4-8.5GHz
 Insertion Loss 5.0dB max
 Isolation 110dB min
 Input&Output VSWR 1.6 max
 RF Input Power 2W(CW)
 Switching Speed 200ns max
 Connectors SMA-Female
 Control Connector JL4-6ZJW
 Voltage/Current +5Vdc@300mA max
 Operating Temperature -55°C~+85°C
 Storage Temperature -55°C~+85°C
 Dimensions $\Phi 92 \times 18$ mm
 Material Aluminum 6061
 Surface Finish Nickel Plated

RoHS Compliant



Drawing not to scale, units:mm

Control Truth Table

TTL Control Voltage Threshold				Low(0)=0V	Signal Path State
				High(1)=3.3V-5V	
C4	C3	C2	C1		
0	0	0	0		J0→J1
0	0	0	1		J0→J2
0	0	1	0		J0→J3
0	0	1	1		J0→J4
0	1	0	0		J0→J5
0	1	0	1		J0→J6
0	1	1	0		J0→J7
0	1	1	1		J0→J8
1	X	X	X		OFF

PART NUMBER
TMPS8-00400850-2S

DESCRIPTION
PIN Diode Switch, SP8T, 0.4-8.5GHz, Absorptive, 2W, SMA-Female

CAGE CODE
SIGNATURE



EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.

www.titan-microwave.com
 Tel: +86 130 866 58398
 Email: sales@titan-microwave.com
 chris@titan-microwave.com