PART NUMBER
TBF-09921032-60S

REV.	DATE	COMMENTS	INITIAL
1	2020/1/25	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 9920-10320MHz
Center Frequency(F_0) 10120MHz
Passband Insertion Loss ..... 2.5dB max
Passband Ripple ..... 1.1dB max
Passband Return Loss ..... 23dB min
Stopband Rejection ..... 60dB min@DC-9.8GHz
..... 60dB min@10.44-24.0GHz
Power Handling ..... 10W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... SMA-Female
Connectors Body ..... Stainless Steel
Housing Material ..... H62 Copper Alloy
Finish ..... Black Painted
Weight 104g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TBF-09921032-60S		Cavity Band Pass Filter, Passband 9.92-10.32GHz Stopband Rejection 60dB, 10W, SMA-Female
CAGE CODE	SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.