PART NUMBER
TBF-1750M20-40S

REV.	DATE	COMMENTS	INITIAL
1	2020/1/2	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 1725-1775MHz
Center Frequency(F_0) 1750MHz
Passband Insertion Loss ..... 1.2dB max
Passband Ripple ..... 0.5dB max
Passband Return Loss ..... 20dB min
Stopband Rejection ..... 40dB min@DC-1705MHz
..... 40dB min@1795-4500MHz
Power Handling ..... 20W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... SMA-Female(Stainless Steel)
Housing Material ..... 6061 Aluminum Alloy
Finish ..... Black Painted
Weight 310g



Drawing not to scale, units:mm[inch]

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TBF-1750M20-40S		Cavity Band Pass Filter, 1725~1775MHz Stopband Rejection 40dB, 20W, SMA-Female
CAGE CODE	SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.