PART NUMBER
TBF-02300260-80S

REV.	DATE	COMMENTS	INITIAL
1	2020/1/2	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 2300-2600MHz
Center Frequency(F_0) 2450MHz
Passband Insertion Loss ..... 0.9dB max
Passband Ripple ..... 0.4dB max
Passband Return Loss ..... 23dB min
Stopband Rejection ..... 80dB min@DC-1900MHz
..... 50dB min@1900-2100MHz
..... 50dB min@2800-3000MHz
..... 80dB min@3000-9500MHz
Power Handling ..... 10W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... SMA-Female(Stainless steel)
Housing Material ..... 6061 Aluminum Alloy
Finish ..... Black Painted
Weight 95g



Drawing not to scale, units:mm[inch]

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER	DESCRIPTION
TBF-02300260-80S	Cavity Band Pass Filter, Passband 2.3~2.6GHz Stopband Rejection 80dB, 10W, SMA-Female
CAGE CODE / SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.