PART NUMBER
TBF-361M366M-80N

REV.	DATE	COMMENTS	INITIAL
1	2020/1/2	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 361-366MHz
Center Frequency(F_0) 363.5MHz
Passband Insertion Loss ..... 0.8dB max
Passband Ripple ..... 0.2dB max
Passband Return Loss ..... 23dB min
Stopband Rejection ..... 80dB min@DC-320MHz
..... 80dB min@407-1500MHz
Power Handling ..... 50W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... N-Female
Housing Material ..... 6061 Aluminum Alloy
Finish ..... Black Painted
Weight 570g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TBF-361M366M-80N		Cavity Band Pass Filter, Passband 361-366MHz Stopband Rejection 80dB, 50W, N-Female
CAGE CODE	SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.