PART NUMBER
TBF-02660268-55S

REV.	DATE	COMMENTS	INITIAL
1	2020/1/25	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 2660-2680MHz
Center Frequency(F_0) 2670MHz
Passband Insertion Loss ..... 1.4dB max
Passband Ripple ..... 0.3dB max
Passband Return Loss ..... 23dB min
Stopband Rejection ..... 55dB min@DC-2615MHz
..... 55dB min@2725-6500MHz
Power Handling ..... 20W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... SMA-Female
Connectors Body ..... Stainless Steel
Housing Material ..... H62 Copper Alloy
Finish ..... Black Painted
Weight 166g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TBF-02660268-55S		Cavity Band Pass Filter, 2.66~2.68GHz Stopband Rejection 55dB, 20W, SMA-Female
CAGE CODE	SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.