PART NUMBER
TBF-880M915M-30N

REV.	DATE	COMMENTS	INITIAL
1	2020/10/2	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 880-915MHz
Center Frequency(F_0) 897.5MHz
Passband Insertion Loss ..... 1.7dB max
Passband Ripple ..... 1.1dB max
Passband Return Loss ..... 20dB min
Stopband Rejection ..... 30dB min@DC-875MHz
..... 30dB min@920-3000MHz
Power Handling ..... 20W max
Impedance ..... 50 Ohms
Operating Temperature ..... -20℃~+60℃
Connectors ..... N-Female
Housing Material ..... Aluminum 6061
Finish ..... Black Painted
Weight 470g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TBF-880M915M-30N		Cavity Band Pass Filter, Passband 880~915MHz Stopband Rejection 30dB, 20W, N-Female
CAGE CODE	SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.