| PART NUMBER |
|---|
| TBF-13101330-65S |

| REV. | DATE | COMMENTS | INITIAL |
|---|---|---|---|
| 1 | 2020/9/8 | ENGINEERING RELEASE | |

## Specifications

RoHS Compliant

Passband Frequency Range ..... 13100-13300MHz
Center Frequency($F_0$) ..... 13200MHz
Passband Insertion Loss ..... 1.7dB max
Passband Ripple ..... 0.6dB max
Passband Return Loss ..... 20dB min
Stopband Rejection ..... 65dB min@DC-12900MHz
..... 65dB min@13500-26000MHz
Power Handling ..... 5W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... SMA-Female(Stainless Steel)
Housing Material ..... H62 Copper Alloy
Finish ..... Black Painted
Weight ..... 105g




Drawing not to scale, units:mm


成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com


| PART NUMBER | | DESCRIPTION |
|---|---|---|
| TBF-13101330-65S | | Cavity Band Pass Filter, Passband 13.1~13.3GHz Stopband Rejection 65dB, 5W, SMA-Female |
| CAGE CODE | SIGNATURE | |


EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.