PART NUMBER
TBF-606M662M-40S

REV.	DATE	COMMENTS	INITIAL
1	2020/9/8	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 606-662MHz
Center Frequency(F_0) 634MHz
Passband Insertion Loss ..... 0.7dB max
Passband Ripple ..... 0.3dB max
Passband VSWR ..... 1.2:1 max
Stopband Rejection ..... 40dB min@DC-554MHz
..... 40dB min@714-2500MHz
Power Handling ..... 50W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... SMA-Female(Stainless Steel)
Housing Material ..... Aluminum 6061
Finish ..... Black Painted
Weight 420g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TBF-606M662M-40S		Cavity Band Pass Filter, Passband 606~662MHz Stopband Rejection 40dB, 50W, SMA-Female
CAGE CODE	SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.