PART NUMBER
TBF-398M402M-45S

REV.	DATE	COMMENTS	INITIAL
1	2020/9/22	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 398-402MHz
Center Frequency(F_0) 400MHz
Passband Insertion Loss ..... 1.8dB max
Passband Ripple ..... 0.3dB max
Passband Return Loss ..... 20dB min
Stopband Rejection ..... 45dB min@DC-388MHz
..... 45dB min@412-1400MHz
Power Handling ..... 20W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors ..... SMA-Female(Stainless Steel)
Housing Material ..... Aluminum 6061
Finish ..... Black Painted
Weight 500g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER	DESCRIPTION
TBF-398M402M-45S	Cavity Band Pass Filter, Passband 398~402MHz Stopband Rejection 45dB, 20W, SMA-Female
CAGE CODE / SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.