


PART NUMBER <b>TBF-50355145-80V</b>	REV.	DATE	COMMENTS	INITIAL
	1	2020/8/23	ENGINEERING RELEASE	

## Specifications

0.6dB Bandwidth .....	50350-51450MHz
Center Frequency( $F_0$ ) .....	50900MHz
Passband Insertion Loss .....	3.0dB max
Passband Flatness .....	0.6dB max(peak-peak)
Passband VSWR .....	1.35:1 max(input/output)
Passband Group Delay .....	2.6ns max(peak-peak)
Passband Group Delay Ripple .....	0.65ns max(peak-peak)
Stopband Rejection .....	80dB min@100-49400MHz
.....	50dB min@52200-70000MHz
Power Handling .....	5W max
Impedance .....	50 Ohms
Operating Temperature .....	-30°C~+70°C
Connectors .....	1.85mm-Male
Housing Material .....	H62 Copper Alloy
Finish .....	Black Painted
Weight .....	45g

RoHS Compliant



Drawing not to scale, units:mm



www.titan-microwave.com  
Tel: +86 130 866 58398  
Email: sales@titan-microwave.com  
chris@titan-microwave.com

PART NUMBER <b>TBF-50355145-80V</b>		DESCRIPTION <b>Cavity Band Pass Filter, Passband 50.35~51.45GHz Stopband Rejection 80dB, 5W, 1.85mm-Male</b>
CAGE CODE	SIGNATURE	
EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.		