PART NUMBER
TBF-13201400-65S

REV.	DATE	COMMENTS	INITIAL
1	2020/1/2	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range	13.2-14GHz
Center Frequency(F_0)	13.6GHz
Passband Insertion Loss	1.0dB max
Passband Ripple	0.4dB max
Passband Return Loss	20dB min
Stopband Rejection	65dB min@DC-12700MHz
	65dB min@14500-26000MHz
Power Handling	5W max
Impedance	50 Ohms
Operating Temperature	-30℃~+70℃
Connectors	SMA-Female(Stainless Steel)
Housing Material	H62 Copper Alloy
Finish	Black Painted
Weight	80g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER	DESCRIPTION
TBF-13201400-65S	Cavity Band Pass Filter, Passband 13.2~14GHz Stopband Rejection 65dB, 5W, SMA-Female
CAGE CODE / SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.