PART NUMBER
TBF-27603060-40K

REV.	DATE	COMMENTS	INITIAL
1	2020/8/21	ENGINEERING RELEASE	

Specifications

RoHS Compliant

Passband Frequency Range 27600-30600MHz
Center Frequency(F_0) 29100MHz
Passband Insertion Loss ..... 1.7dB max
Passband Ripple ..... 0.7dB max
Passband Return Loss ..... 18dB min
Stopband Rejection ..... 40dB min@DC-27180MHz
..... 40dB min@31020-48000MHz
Power Handling ..... 5W max
Impedance ..... 50 Ohms
Operating Temperature ..... -30℃~+70℃
Connectors 2.92mm-Female
Housing Material ..... H62 Copper Alloy
Finish ..... Black Painted
Weight 80g



Drawing not to scale, units:mm

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com
Tel: +86 130 866 58398
Email: sales@titan-microwave.com
chris@titan-microwave.com

PART NUMBER		DESCRIPTION
TBF-27603060-40K		Cavity Band Pass Filter, Passband 27.6~30.6GHz Stopband Rejection 40dB, 5W, 2.92mm-Female
CAGE CODE	SIGNATURE	

EXCEPT AS OTHERWISE PROVIDED BY CONTRACTOR THIS DRAWING OR SPECIFICATION IS PROPERTY OF TITAN MICROWAVE INC. IT IS ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED OR USED AS THE BASIS.