

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/3/21	C. Chen

TECHNICAL DATA

► Electrical Data

Frequency Range	50-1000MHz
Max Output Power(Psat, CW)	≥47dBm
Gain	≥45dB
Gain Flatness	≤4±1dB
VSWR Input	≤1.8
Input Power	3±2dBm
Max Input Power	+10dBm
Spurious	≤-65dBc
Harmonic	≥-10dBc
Impedance	50 Ohms
PTT Port	Default OFF, 3.3-5V ON
Temperature Protection	Over 80°C protection with open circuit protection
Operation Current	≤7A
VCC/Current Reference	+28V/15A
Max Operation Voltage	+31V


► Mechanical Data

Dimensions	181.07×78.92×26.2mm
Input Connector	SMA-Female
Output Connector	N-Female
28V Power Supply Interface	Feedthru Capacitor
Package	1 piece/box

► Environmental Data

Operating Temperature	-25°C~+55°C
-----------------------	-------------

! Stress above these ratings may cause permanent damage to the device
Radiator/Heatsink required during operation or test



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/03/22		
ENGINEER: J. Zhu 21/03/22		
APPROVED: C. Chen 21/03/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:


Power Amplifier, 50-1000MHz, Gain 45dB, Output Power 47dBm, +28V, SMA/N-Female

PART No.:

TMPA-00050100-4547

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------