


REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/5/20	C. Chen

TECHNICAL DATA

► Electrical Data(50Ω, 25℃)

Frequency Range	1~30MHz
Output Power(CW)	56dBm min, 57dBm typ
Output Power(P1dB)	52dBm typ
Gain	60dB min, 61dB typ
Gain Flatness	±0.5dB typ
Gain Variation@-30℃~+70℃	±3dB typ
Input VSWR	1.5:1 typ
Max Input Power	+5dBm
Harmonic	-15dBc typ, -9dBc max
2-Tone Intermodulation(IMD)	-25dBc typ(47dBm/Tone, Δ=1MHz)
Spurious	-60dBc max
Isolation	-50dB typ
Operating Voltage	+46V~+50V
Operating Current(VCC=48V)	2.7A typ, 22A max



► Mechanical Data

Dimensions	230×130×30mm
Input Connector	SMA-Female
Output Connector	N-Female
DC Power/Interface Connector	9-Pin D-Sub

► Environmental Data

Operating Temperature	-30℃~+60℃
Storage Temperature	-50℃~+105℃

! Stress above these ratings may cause permanent damage to the device
Radiator/Heatsink required during operation or test

DC Power Connector, 9-Pin D-Sub, Female

Pin	Name	Function	Specifications
1	+48V	Input	+46~+50VDC
2	+48V	Input	+46~+50VDC
3	+48V	Input	+46~+50VDC
4	GND	Input	Ground
5	GND	Input	Ground
6	+48V	Input	+46~+50VDC
7	Temp Alarm	Output	Pin will be latched to logic HIGH, and PA Off when case temperature is more than 70℃
8	PA-Enable	Input	Applying logic LOW disables drains of amplifiers
9	GND	Input	Ground

DRAWN: L. Ma 20/05/23		
ENGINEER: J. Zhu 20/05/23		
APPROVED: C. Chen 20/05/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:
Power Amplifier, 1-30MHz, Gain 60dB,
Output Power 56dBm,
+48V, SMA/N-Female

PART No.:
TMPA-1M30M-6056

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY