

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/19	C. Chen

## TECHNICAL DATA

### Electrical Data

Frequency Range	1100-1700MHz
Max Output Power(Psat)	≥50dBm
Gain	≥49dB
Gain Flatness	≤2±1dB
VSWR Input	≤2.0
Input Power	2±2dBm
Max Input Power	+8dBm
Spurious	≤-65dBc
Harmonic	≤-12dBc
Impedance	50 Ohms
PTT Port	Default OFF, 3.3~5V ON
Temperature Protection	Over 80℃ protection with open circuit protection
Operation Current	≤9~12.8A
Operation Voltage	+28V~+32V
VCC/Current Reference	32V/15A


### Mechanical Data

Dimensions	238×128×26.3mm
Input Connector	SMA-Female(right angle)
Output Connector	SMA-Female
28V Power Supply Interface	5557-4.2mm power-6
Package	1 piece/box
Weight	≤2Kg

### Environmental Data

Operating Temperature	-40℃~+55℃
-----------------------	-----------

! Stress above these ratings may cause permanent damage to the device  
Radiator/Heatsink required during operation or test



DRAWN: L. Ma 19/04/22		
ENGINEER: J. Zhu 19/04/22		
APPROVED: C. Chen 19/04/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

#### TITLE:

Power Amplifier,  
1.1~1.7GHz, Gain 49dB,  
Output Power 50dBm,  
+32V, SMA-Female

#### PART No.:

TMPA-01100170-4950



[www.titan-microwave.com](http://www.titan-microwave.com)



DIMENSIONS IN MILLIMETERS(mm)

SIZE:  
A4

SCALE:

SHEET:  
1/1

REV:  
A

#### Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY