

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/12	C. Chen

TECHNICAL DATA

Electrical Data


Stop Band Frequency	728~821MHz
Stop Band Attenuation	≥50dB
Pass Band Frequency	DC~693MHz&875~2400MHz
Pass Band Insertion Loss	≤1.0dB
Pass Band VSWR	≤1.5:1@330~693MHz&875~2400MHz ≤1.8:1@DC~330MHz
Power Handling	≤10W
Impedance	50 Ohms

Mechanical Data

Dimensions	265×74×28mm
Connectors	SMA-Female
Connector Material	Stainless Steel
Surface Finish	Black Painted

Environmental Data

Temperature Range	-10℃~+50℃
-------------------	-----------



DRAWN: L. Ma 12/09/23		
ENGINEER: J. Zhu 12/09/23		
APPROVED: C. Chen 12/09/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:
Band Reject Filter,
728~821MHz, Stop Band
Rejection 50dB, 10W,
SMA-Female

PART No.:
TRF-728M821M-50S

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -

www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
--------------------	---------------	----------------------	------------------

Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY