

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/12	C. Chen

TECHNICAL DATA

► Electrical Data


Stop Band Frequency	1300~1500MHz
Stop Band Attenuation	≥40dB
Pass Band Frequency	DC~1240MHz & 1560~3900MHz
Pass Band Insertion Loss	≤1.5dB
Pass Band VSWR	≤1.5:1@550~1240MHz & 1560~3900MHz ≤1.8:1@DC~550MHz
Power Handling	≤10W
Impedance	50 Ohms

► Mechanical Data

Dimensions	234×50×28mm
Connectors	SMA-Female
Connector Material	Stainless Steel
Surface Finish	Black Painted

► Environmental Data

Temperature Range	-30℃~+70℃
-------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 12/09/23		
ENGINEER: J. Zhu 12/09/23		
APPROVED: C. Chen 12/09/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

Band Reject Filter,
1.3~1.5GHz, Stop Band
Rejection 40dB, 10W,
SMA-Female

PART No.:

TRF-01300150-40S



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------