

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/12	C. Chen

TECHNICAL DATA

► Electrical Data


Stop Band Frequency	2100~2190MHz
Stop Band Attenuation	≥60dB
Pass Band Frequency	DC~2065MHz & 2225~5300MHz
Pass Band Insertion Loss	≤2.0dB
Pass Band VSWR	≤1.5:1
Power Handling	≤20W
Impedance	50 Ohms

► Mechanical Data

Dimensions	209×40×22mm
Connectors	SMA-Female
Connector Material	Copper H59
Surface Finish	Black Painted



► Environmental Data

Temperature Range	-30℃~+70℃
-------------------	-----------



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 12/09/23	TITLE: Band Reject Filter, 2.1~2.19GHz, Stop Band Rejection 60dB, 20W, SMA-Female	 成都巨人微波 TITAN MICROWAVE INC. - A Professional RF & Microwave Components Supplier -				
ENGINEER: J. Zhu 12/09/23				www.titan-microwave.com		
APPROVED: C. Chen 12/09/23		 DIMENSIONS IN MILLIMETERS(mm)				
TOLERANCE UNLESS OTHERWISE SPECIFIED		PART No.: TRF-02100219-60S	SIZE: A4	SCALE:	SHEET: 1/1	REV: A
x	±0.50		[0.019"]			
.x	±0.20	[0.008"]				
.xx	±0.10	[0.004"]				
ANGLES	±1°					