

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/12	C. Chen

## TECHNICAL DATA

### ► Electrical Data


Stop Band Frequency	1920~1980MHz
Stop Band Attenuation	≥60dB
Pass Band Frequency	DC~1895MHz & 2005~5400MHz
Pass Band Insertion Loss	≤1.0dB@DC~1870MHz & 2030~5400MHz ≤1.7dB@1870~1895MHz & 2005~2030MHz
Pass Band VSWR	≤1.5:1
Power Handling	≤20W
Impedance	50 Ohms

### ► Mechanical Data

Dimensions	245×45×22mm
Connectors	SMA-Female
Connector Material	Copper H59
Surface Finish	Black Painted

### ► Environmental Data

Temperature Range	-20℃~+60℃
-------------------	-----------



DRAWN: L. Ma 12/09/23		
ENGINEER: J. Zhu 12/09/23		
APPROVED: C. Chen 12/09/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

**TITLE:**  
Band Reject Filter,  
1.92~1.98GHz, Stop  
Band Rejection 60dB,  
20W, SMA-Female

**PART No.:**  
TRF-01920198-60S



[www.titan-microwave.com](http://www.titan-microwave.com)



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------

#### Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY