

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2023/9/12	C. Chen

## TECHNICAL DATA

### ► Electrical Data


Stop Band Frequency	3400~3800MHz
Stop Band Attenuation	≥45dB
Pass Band Frequency	DC~3180MHz & 4020~8000MHz
Pass Band Insertion Loss	≤2.5dB
Pass Band VSWR	≤1.7:1
Power Handling	≤10W
Impedance	50 Ohms

### ► Mechanical Data

Dimensions	141×32×16mm
Connectors	SMA-Female
Connector Material	Copper H59
Surface Finish	Black Painted


### ► Environmental Data

Temperature Range	-20℃~+60℃
-------------------	-----------




DRAWN: L. Ma 12/09/23		
ENGINEER: J. Zhu 12/09/23		
APPROVED: C. Chen 12/09/23		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE: Band Reject Filter, 3.4~3.8GHz, Stop Band Rejection 45dB, 10W, SMA-Female	
PART No.: TRF-03400380-45S	



**成都巨人微波**  
**TITAN MICROWAVE INC.**  
- A Professional RF & Microwave Components Supplier -

[www.titan-microwave.com](http://www.titan-microwave.com)



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------

- Notes:
- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
  - CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY