

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2024/5/17	C. Chen

TECHNICAL DATA

► Electrical Data


Stop Band Frequency	3300~4200MHz
Stop Band Attenuation	≥70dB
Pass Band Frequency	DC~3200MHz & 4300~6500MHz
Pass Band Insertion Loss	≤2.0dB
Pass Band VSWR	≤2.0:1
Power Handling	20W
Impedance	50 Ohms

► Mechanical Data

Dimensions	164×32×20mm
Connectors	SMA-Female
Surface Finish	Black Painted



► Environmental Data

Operating Temperature	-30℃~+70℃
Storage Temperature	-55℃~+85℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 17/05/24	TITLE: Band Reject Filter, 3.4~4.2GHz, Stop Band Rejection 70dB, 20W, SMA-Female	 成都巨人微波 TITAN MICROWAVE INC. <small>- A Professional RF & Microwave Components Supplier -</small>				
ENGINEER: J. Zhu 17/05/24				www.titan-microwave.com		
APPROVED: C. Chen 17/05/24		 DIMENSIONS IN MILLIMETERS(mm)				
TOLERANCE UNLESS OTHERWISE SPECIFIED		PART No.:	SIZE:	SCALE:	SHEET:	REV:
x	±0.50 [0.019"]					
.x	±0.20 [0.008"]					
.xx	±0.10 [0.004"]					
ANGLES	±1°					