

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

## TECHNICAL DATA

### ► Electrical Data


Frequency Range	10-6000MHz
Insertion Loss (excluding theoretical loss 9.0dB)	4.4dB max
Input Port VSWR	7.5:1 max@10~260MHz 1.45:1 max@260~6000MHz
Output Port VSWR	5.0:1 max@10~120MHz 1.25:1 max@120~6000MHz
Isolation	7dB min@10~260MHz 20dB min@260~6000MHz
Amplitude Balance	±0.4dB
Phase Balance	±8°
Impedance	50 Ohms
Power Rating	20W(as a splitter)
Power Rating	1W(as a combiner)

### ► Mechanical Data

Input/Output Connectors	SMA-Female
Dimensions	176×120×12mm
Surface Finish	Gray Painted
Weight	580g

### ► Environmental Data

Operating Temperature	-45℃~+85℃
-----------------------	-----------



DRAWN: L. Ma 21/12/22		
ENGINEER: J. Zhu 21/12/22		
APPROVED: C. Chen 21/12/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:  
Power Divider, 8 Way,  
0.01~6GHz, 20W, SMA-  
Female

PART No.:  
TMPD8-00010600-20S



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------

#### Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY