

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

## TECHNICAL DATA

### Electrical Data


Frequency Range	800-2500MHz
Insertion Loss (excluding theoretical loss 10.8dB)	2.2dB max
Input Port VSWR	1.18 typ, 1.4 max
Output Port VSWR	1.12 typ, 1.3 max
Isolation	18dB min
Amplitude Balance	±0.8dB
Phase Balance	±8°
Impedance	50 Ohms
Power Rating	20W(as a splitter)
Power Rating	1W(as a combiner)

### Mechanical Data

Input/Output Connectors	SMA-Female
Dimensions	165×125×12mm
Surface Finish	Sandblasting natural color conductive oxidation

### Environmental Data

Operating Temperature	-35°C~+75°C
-----------------------	-------------



DRAWN: L. Ma 21/12/22		
ENGINEER: J. Zhu 21/12/22		
APPROVED: C. Chen 21/12/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

**TITLE:**  
Power Divider, 12 Way,  
0.8~2.5GHz, 20W, SMA-  
Female

**PART No.:**  
TMPD12-00800250-20S



[www.titan-microwave.com](http://www.titan-microwave.com)



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------

#### Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY