

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/4/16	C. Chen

TECHNICAL DATA

► Electrical Data


Frequency Range	2~8GHz
Nominal Coupling	30±1.0dB
Insertion Loss	0.5dB max
VSWR Primary	1.2:1 typ, 1.25:1 max
VSWR Secondary	1.2:1 typ, 1.25:1 max
Directivity	18dB min, 22dB typ
Frequency Sensitivity	±0.5dB typ, ±0.7dB max
Impedance	50 Ohms
Power Rating	50W

► Mechanical Data

Dimensions	86×17×11mm
Input/Output Connectors	SMA-Female
Coupled Connector	SMA-Female
Housing Material	Aluminum 6061
Surface Finishing	Gray Painted

► Environmental Data

Operating Temperature	-40℃~+70℃
Storage Temperature	-50℃~+85℃



Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 16/04/22		
ENGINEER: J. Zhu 16/04/22		
APPROVED: C. Chen 16/04/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

Dual Directional Coupler,
2~8GHz,
Coupling 30dB, 50W,
SMA-Female

PART No.:

TDDC-02000800-30S50



www.titan-microwave.com



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------