

TA480

Low Loss Phase Stable Cable Assembly DC~26.5GHz



Features

- Low Loss
- High Phase Stability
- Excellent Performance
- Well Durability
- Suitable for All Kinds of Harsh Environment

Applications

- Laboratory
- Wireless Communications
- Phased Array Radar
- Avionics

Specifications

Electrical

Operating Frequency	DC~26.5GHz
Cutoff Frequency	31GHz
Impedance	50Ω
Velocity of Propagation	83%
Screening Effectiveness	90dB min
PIM	-155dBc
Voltage Rating	1500V, DC
Phase Stability	<750ppm@-55°C~+85°C

Environmental & Mechanical

Operating Temperature	-55°C~+165°C
Min Bending Radius/Single	24.00 mm
Min Bending Radius/Repeated	48.00 mm
Weight	55g/m

Attenuation@25°C & Power@40°C(sea level)

Frequency(GHz)	1	2	3	6	8	10	12.4	18	26.5
Attenuation(dB/100m)	24.1	34.2	42.1	60.1	69.7	78.3	87.6	106.6	130.8
Power Handling(W)	1050	738	600	420	362	323	288	237	193

Construction

Inner Conductor	Solid Silver-plated Copper	1.40mm
Dielectric	Low Density PTFE	3.80mm
Inner Shield	Silver-plated Copper Tape	3.95mm
Outer Shield	Silver-plated Copper Braid	4.35mm
Jacket	PFA	4.80mm

Outline



Ordering Information

TA480 - 26.5 - SFSF - 1

Cable

Operating Frequency(GHz)

RF Connectors(S:SMA)

SS: SMA male to SMA male

SSF: SMA male to SMA female

SFSF: SMA female to SMA female

Overall Length(meter(s))