

REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

## TECHNICAL DATA

### ► Electrical Data


Frequency Range	100~200MHz
Insertion Loss (excluding theoretical loss 12.0dB)	1.0dB max
Input Port VSWR	1.18 typ, 1.30 max
Output Port VSWR	1.12 typ, 1.20 max
Isolation	18dB min, 24dB typ
Amplitude Balance	±0.3dB
Phase Balance	±3°
Impedance	50 Ohms
Power Rating	200W(as a splitter) 20W(as a combiner)

### ► Mechanical Data

Input/Output Connectors	N-Female
Housing Material	Aluminum
Dimensions	654×392×22mm
Surface Finish	Conductive Oxidation

### ► Environmental Data

Operating Temperature	-35°C~+75°C
-----------------------	-------------



#### Notes:

- ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
- CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22		
ENGINEER: J. Zhu 21/12/22		
APPROVED: C. Chen 21/12/22		
TOLERANCE UNLESS OTHERWISE SPECIFIED		
x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:  
Power Divider, 16 Way,  
100~200MHz, 200W,  
N-Female

PART No.:  
TMPD16-00100020-200N



[www.titan-microwave.com](http://www.titan-microwave.com)



DIMENSIONS IN MILLIMETERS(mm)

SIZE: A4	SCALE:	SHEET: 1/1	REV: A
-------------	--------	---------------	-----------