REV	DESCRIPTION OF REVISION	By	DATE	APPROVED
A	INITIAL RELEASE	C. Cai	2022/12/21	C. Chen

TECHNICAL DATA

▶ Electrical Data

Frequency Range	1.5~30MHz
Insertion Loss (excluding theoretical loss 9.0dB)	1.6dB max
Input Port VSWR	1.8:1 max@1.5~5MHz, 1.4:1 max@5~30MHz
Output Port VSWR	1.8:1 max@1.5~5MHz, 1.4:1 max@5~30MHz
Isolation	18dB min, 26dB typ
Amplitude Balance	±0.4dB
Phase Balance	±6°
Impedance	50 Ohms
Power Rating	1W(as a splitter) 0.5W(as a combiner)

▶ Mechanical Data

Input/Output Connectors	SMA-Female
Dimensions	120×32×13mm
Surface Finish	Conductive Oxidation
Weight	200g

▶ Environmental Data

Operating Temperature	-35℃~+75℃



Notes:

1. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME
2. CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY

DRAWN: L. Ma 21/12/22

ENGINEER: J. Zhu 21/12/22

APPROVED: C. Chen 21/12/22

TOLERANCE UNLESS OTHERWISE SPECIFIED

x	±0.50	[0.019"]
.x	±0.20	[0.008"]
.xx	±0.10	[0.004"]
ANGLES	±1°	

TITLE:

Power Divider
8 Way, 1.5~30MHz, 1W,
SMA-Female

PART No.:

TMPD8-1.5M0003-1S

成都巨人微波
TITAN MICROWAVE INC.
- A Professional RF & Microwave Components Supplier -
www.titan-microwave.com

DIMENSIONS IN MILLIMETERS(mm)

SIZE:	SCALE:	SHEET:	REV:
A4		1/1	A